




cometo

WIRE AND CABLE EQUIPMENT


UNITA' DI TAGLIO

CUTTER UNIT



TAG10





Per filo tondo, profilato e barre.

Azionamento pneumatico, idraulico o elettronico con motore brushless (per versione con motore brushless contattare ufficio tecnico Cometo per dimensionamento corretto)

Struttura in acciaio e fusioni di ghisa

Design compatto

Sistema di lubrificazione centralizzato

Parti facilmente intercambiabili per adattarsi a diversi profili

Coltello in acciaio temprato e rettificato

CAPACITA' DI TAGLIO: 1mm -12 mm dia.

PRESSIONE IN ENTRATA:

Unità pneumatica : 1kg/cm² (min)- 6 kg/cm² (max)

Unità idraulica : 50kg/cm² (min)- 150 kg/cm² (max)

PRESSIONE DI TAGLIO:

(al punto di contatto con il materiale)

Unità pneumatica : 1.800 kg/cm²

Unità idraulica : 4.500 kg/cm²

INTERVALLO DI TAGLIO: circa 0.4 secondi per materiale con dia.12mm

For wire rod and shaped wire

Pneumatic or hydraulic actuator. Available also with electronic driving with brushless motor (in case of brushless motor version, please contact Cometo technical office to choose correct power)

Cast iron frame and steel construction and compact design

Centralized oil lubrication system

Easy interchangeability of parts for different material profiles

Hardened and ground toolsteel cutting blades and material guides

Additional material guides for profiled materials

CUTTING CAPACITY: 1mm -12 mm dia.

INPUT PRESSURE:

Pneumatic unit : 1kg/cm² (min) - 6 kg/cm² (max)

Hydraulic unit : 50kg/cm² (min) - 150 kg/cm² (max)

CUTTING PRESSURE

(at contact point with material)

Pneumatic unit : 1.800 kg/cm²

Hydraulic unit : 4.500 kg/cm²

CUTTING TIME : approx 0.4 seconds for 12mm material

COMETO DI TOCCHETTI PIETRO & C. s.n.c.

VIA CABELLA LATTUADA, 41 -23841- ANNONE DI BRIANZA, LC- ITALY

TPH +39-(0)341-263090 FAX +39-(0)341-260927 www.cometo.eu E-MAIL p.tocchetti@cometo.eu